

Diaphragm Liquid Transfer Pump LIQUIPORT® NF 300 S KNF

[Product in eShop](#)

[Home](#) / [Assortment](#) / [Research & Development](#) / [Liquid Handling](#) / [Pumps](#) / [Diaphragm Liquid Transfer Pump LIQUIPORT® NF 300 S KNF](#)

Product Data

Chemically resistant liquid transfer diaphragm pump. Offers wetted material combinations for optimal chemical resistance. Manual control of flow rate with LED indicator.

- Flow Rate: 0.5–3 l/min
- Pressure (max.): 1 bar (rel.)
- Small footprint
- Simple, intuitive operation
- Manual control
- Self-priming, can run dry
- Suction Height (max.) 3 mWg
- Weight 1.5 kg
- Valve Material Options: FFKM
- Diaphragm Material Options: PTFE coated
- Pump Head Material Options: PTFE, PP, PVDF

Item No.	type no.	material of the pump head	Price
17.8621.20	NF 300 KT.18S	PP	CHF 1'039.00
17.8621.21	NF 300 TT.18S	PVDF	CHF 1'319.00

* The prices are non-binding and are to be understood as selling prices in Swiss francs without value added tax (VAT), as well as all other fees, charges and taxes. The prices displayed in the eShop may differ from the PDF file due to regular updates.

** Please note that when ordering chemicals and detergents, transport and packaging costs for hazardous goods as well as legally prescribed fees are charged. These will be shown in detail on the order confirmation, which you will receive in addition to the confirmation of receipt.

*** Further information such as technical information and safety data sheets can be found online in our eShop.

**** The PDF file was created on www.huberlab.ch on 04.05.2026 at 23:42 oclock.

www.huberlab.ch