

Technical Datasheet

Date: 11.11.16

Page 1 of 1

		EN ISO certified
Article - No:	08-512-4003	Revision: 1
Remarks	The survival rate of bacteria corresponds to the standard: DIN 58942-4 The filling amount of the liquid to be examined must be 10 ml, with a maximum tolerance of +/- 10%	single use only

Specification

Product	EXACTOBAC-U® urisog, with fitted screw cap PE, 10ml, urisog, tube PP Ø14,5x101 mm, with lyophilized urine stabilizer, tube transparent, cap yellow, CE/IVD
Classification	CE/IVD
Colour	tube transparent, cap yellow
Nominal Capacity	10ml
Material Characteristics	tube: polypropylene (PP) cap: polyethylene (PE) piston: polyethylene (PE)
Product Characteristics	biologically inert physiologically harmless media: lyophilisate on boric acid sturdy, shock resistant high chemical resistance
Shelf - Life	60 months at controlled storage conditions
Packaging	pcs per bag: 1.000 pcs per carton: 1.000 pcs per pallet: 24.000
Minimum order qty.	1.000 pcs
Storage	in dry condition: 40% - 60% rel. humidity bags and cartons originally closed storage temperature +10°C to maximal +30°C pallets cannot be stacked
Approved by nerbe plus quality department	