

Technical Datasheet

Date: 11.11.16

Page 1 of 1

		EN ISO certified
Article - No:	08-522-4003	Revision: 1
Remarks	The survival rate of bacteria corresponds to the standard: DIN 58942-4 The filling amount of the liquid to be examined must be 10 ml, with a maximum tolerance of +/- 10%	single use only

Specification

Product	EXACTOBAC-U®, with fitted screw cap PE, 20ml, urine transport tube PP, Ø25x107 mm, with label, with lyophilised urine stabilizer, skirted, max. RCF 5.000g, CE/IVD
Classification	CE/IVD
Dimensions	outer diameter: 25,00 mm (+/- 0,2 mm) height: 107,00 mm (+/- 0,2 mm)
Nominal Capacity	20ml
Material Characteristics	tube: polypropylene (PP) cap: polyethylene (PE)
Centrifugation	max. RCF 5.000g
Product Characteristics	biologically inert physiologically harmless media: lyophilisate on boric acid sturdy, shock resistant high chemical resistance transparent tube and yellow cap
Shelf - Life	60 months at controlled storage conditions
Packaging	pcs per bag: 500 pcs per carton: 500 pcs per pallet: 12.000
Minimum order qty.	500 pcs
Storage	in dry condition: 40% - 60% rel. humidity bags and cartons originally closed storage temperature +10°C to maximal +30°C pallets cannot be stacked
Approved by nerbe plus quality department	